


# Marquette-Hellige CardioSys Tango Interface Notes

You can setup the Tango with your stress system using the following directions. You will need the ECG trigger and RS-232 cables specified below.

- The ECG trigger cable is required for the Tango monitor to be able to take a BP measurement.
- You will need the RS-232 cable to establish communication between the Tango and your stress system. This cable allows your stress system to prompt the Tango when it needs a BP measurement. In addition, it allows the BP measurements taken by the Tango to be transferred to your stress system display and reports.



## 1. Plugging in the ECG trigger cable

To connect the Tango to the ECG trigger of the CardioSys, you must use a **Tango monitor with an internal ECG board**.

Connect: the ECG trigger cable, SunTech part #91-0016-00 (AAMI connector to 3 pin Franz Binder connector)

From: the Internal ECG connection on the rear panel of the Tango (AAMI connector)

To: the output socket (using a small plastic connector) on the small female connector on the right side of the card well at the back of the stress system (3 pin Franz Binder connector)

## 2. Plugging in the RS-232 cable

Connect: the RS-232 cable, SunTech part #91-0013-00 (9 pin female to 9 pin female)

From: the RS-232 connection on the rear panel of the Tango (9 pin female)

To: the COM 1, 2, or 3 port on the back of the stress system (9 pin female)

3. Setting up the Tango monitor
  - a. Turn on the Tango using the switch at the rear top left corner of the Tango.
  - b. Once the operating screen is displayed, press the *MENU/SELECT* button. Use the UP or DOWN buttons to select **Utilities** and press the menu button.
  - c. Use the arrow buttons to select **Device** and press the *MENU/SELECT* button to edit. Choose **SUNTECH** using the arrow buttons and press the select button to confirm the choice.
  - d. Select **ECG trigger** and press the select button to edit. Choose **INTERNAL** and press the select button to confirm the choice.
  - e. Select **Exit** twice to return to the operating screen.
  
4. Setting up the stress system
  - a. Turn the CardioSys on and at the main screen, click on the “running man” icon. This will present the **Retrieve Patient** screen.
  - b. Select any patient and press **OK**. At the **Test Demographics** screen press **Cancel**.
  - c. Select **Defaults** and proceed to **Page 2**. Select the **1mv signal** by ensuring that an ‘x’ appears in the box.
  - d. Select the **BP Monitor** as **BP METER 1**
  - e. For **Port**, choose the COM port you have connected the cable to i.e. **COM 1, COM 2** or **COM 3**
  - f. Select **OK** to exit.